

Flow Release Pulling Tool (GS)

The Wellpro Group Flow Release Pulling Tool (GS) is a reliable and cost effective means of retrieving tools with an internal 'GS' style fishing neck.

The tool can be utilised by setting down weight to engage fish allowing the weight applied to the tool to overcome the internal spring force. To release the overshot from the fish simply apply down weight on the BHA while circulating at a pre-determined flow rate through the tool.

The tool can also be operated by circulating at a pre-determined flow rate through an adjustable orifice. This creates an internal pressure that activates an unbalanced piston allowing the spear grapple to become de-supported prior to entering the fish. This method also allows for jetting to clean fish area.

Specifications and features

- Hydraulically activated
- High strength for jarring operations
- Means of engaging, locating and pulling on standard, internal fishing necks
- Variety of nozzle sizes to suit specific flow rates and operating parameters
- Simple robust design

Tool Size (in)	1-1/2" GS	2" GS	2-1/2" GS	3" GS	3-1/2" GS
End Connection	1" AMMT	1-1/4" AMMT	1-1/2" AMMT	2-3/8" PAC	2-3/8" PAC
Tensile Strength (lbs)	30,000	42,000	53,100	72,000	102,000
Length (ft)	1.02	1.31	1.28	1.46	1.69
Max Working Pressure (psi)	5,000	5,000	5,000	5,000	5,000

The equipment specifications and information advised in this document are for information only and may be liable to change without notice. Additional tool sizes and connection variations are available upon request.

